
SPECIFICATION SHEET

COLLECTION: OMIKA PRODUCT CODE: OMI-100M/CC-C/P





The flow rate displayed is calculated using ideal system conditions. This result should only be taken as an indication as the flow rate may vary depending on the specific in-situ configuration.

TAP TYPE

Basin Mixer

FINISH Chrome

COLLECTION NAME Omika

GUARANTEE 15 Year Guarantee

PLUMBING SYSTEM SUITABILITY

Pumped System, Combination Boiler, Pressurised System

MINIMUM OPERATING PRESSURE

1.0 Bar MP

MAXIMUM OPERATING PRESSURE

5.0 Bar HP

MOUNTING

Deck Mounted

WASTE With Universal Basin Waste

tel: 01934 744466 email: sales@vado.com www.vado.com

WHERE INSPIRATION FLOWS



SPECIFICATION SHEET

COLLECTION: OMIKA PRODUCT CODE: OMI-100M/CC-C/P

RECOMMENDED FLOW REGULATOR

4 l/m flow regulator fitted as standard

WITH ECOTURN COLD START TECHNOLOGY

No

WITH WATER FLOW STRAIGHTENER

No

WITH WATER FLOW AERATOR

Yes

CONNECTIONS / FITTINGS

2 x 1/2" 400mm flexipipe connections

DECK HOLE DRILL DIAMETER 35mm

SPARE PARTS 2 x FL-401-RTC

NOTES 1/4 turn ceramic disc valves


tel: 01934 744466 email: sales@vado.com www.vado.com

WHERE INSPIRATION FLOWS



TECHNICAL DRAWING

COLLECTION: OMIKA PRODUCT CODE: OMI-100M/CC-C/P



tel: 01934 744466 email: sales@vado.com www.vado.com

WHERE INSPIRATION FLOWS

