SPECIFICATION SHEET

COLLECTION: OMIKA
PRODUCT CODE: OMI-100M/CC-C/P

Flow Rates
(for "mixed" measurements)

TAP TYPE
Basin Mixer

MAXIMUM OPERATING PRESSURE
5.0 Bar LP

COLLECTION NAME
Omika

GUARANTEE
15 Year Guarantee

FINISH
Chrome

WITH ECOTURN COLD START TECHNOLOGY
No

RECOMMENDED FLOW REGULATOR
4 l/m flow regulator fitted as standard

NOTES
1/4 turn ceramic disc valves

MINIMUM OPERATING PRESSURE
1.0 Bar MP

SPECIFICATION SHEET

COLLECTION: OMIKA
PRODUCT CODE: OMI-100M/CC-C/P

WITH WATER FLOW STRAIGHTENER

No

WITH WATER FLOW AERATOR

Yes

CONNECTIONS / FITTINGS

2 x 1/2″ 400mm flexipipe connections

SPARE PARTS

2 x FL-401-RTC

DECK HOLE DRILL DIAMETER

35mm

WASTE

with Universal Basin Waste

MOUNTING

Deck Mounted

PLUMBING SYSTEM SUITABILITY

Pumped System, Combination Boiler, Pressurised System

tel: 01934 744466
email: sales@vado.com
www.vado.com

WHERE INSPIRATION FLOWS
TAPS | SHOWERS | ACCESSORIES

VADO

TECHNICAL DRAWING

120

50

33

105

19

48

78

100.5

ø63

Min.0 - Max.63

1"1/4

ø62

WHERE INSPIRATION FLOWS
TAPS | SHOWERS | ACCESSORIES

VADO