
SPECIFICATION SHEET

COLLECTION: SHOWERING SOLUTIONS, SIRKEL

PRODUCT CODE: AX-SIR-149T-CP





The flow rate displayed is calculated using ideal system conditions. This result should only be taken as an indication as the flow rate may vary depending on the specific in-situ configuration.

VALVE TYPE

Exposed

HANDLES

2 Handle

WITH ALL-FLOW FUNCTION

No

WITH INTEGRATED DIVERTER

No

COMPATIBLE WITH STUDFAST

No

WITH BLEED VALVE FOR SYSTEM FLUSH ON INSTALLATION

Nο

WITH SHOWER KIT

No

INCLUDES MORTAR / TILE GUARD

No

COMPATIBLE WITH EASY-FIX BRACKETS

Yes

tel: 01934 744466 email: sales@vado.com

www.vado.com

WHERE INSPIRATION FLOWS



SPECIFICATION SHEET

COLLECTION: SHOWERING SOLUTIONS, SIRKEL PRODUCT CODE: AX-SIR-149T-CP

WITH THERMOSTATIC TECHNOLOGY

Yes

CONNECTIONS / FITTINGS

1/2" x 3/4" x 50mm eccentrics

SPARE PARTS

Thermostatic Cartridge S-701-31S Flow Cartridge H-202-RTC

MOUNTING

Wall Mounted

PLUMBING SYSTEM SUITABILITY

Pumped System, Combination Boiler, Pressurised System

COLLECTION NAME

Showering Solutions, Sirkel

FINISH

Chrome

MINIMUM OPERATING PRESSURE

1.0 Bar MP

MAXIMUM OPERATING PRESSURE

5.0 Bar HP

GUARANTEE

10 Year Guarantee

tel: 01934 744466 email: sales@vado.com www.vado.com





TECHNICAL DRAWING

COLLECTION: SHOWERING SOLUTIONS, SIRKEL

PRODUCT CODE: AX-SIR-149T-CP

