
# SPECIFICATION SHEET

COLLECTION: DX ELEMENTS

PRODUCT CODE: ELE-148D/2/SQ-CP





The flow rate displayed is calculated using ideal system conditions. This result should only be taken as an indication as the flow rate may vary depending on the specific in-situ configuration.

#### SHOWER TYPE

Shower Valve

### **VALVE TYPE**

Concealed

### STYLE

Cross Handles

### ORIENTATION

Vertical

#### NUMBER OF OUTLETS

2 Outlet

#### **HANDLES**

2 Handle

#### WITH ALL-FLOW FUNCTION

No

# WITH INTEGRATED DIVERTER

Yes

# COMPATIBLE WITH STUDFAST

Yes

tel: 01934 744466 email: sales@vado.com

www.vado.com

WHERE INSPIRATION FLOWS



# SPECIFICATION SHEET

COLLECTION: DX ELEMENTS

PRODUCT CODE: ELE-148D/2/SQ-CP

### WITH BLEED VALVE FOR SYSTEM FLUSH ON INSTALLATION

Yes

WITH SHOWER KIT

Νo

INCLUDES MORTAR / TILE GUARD

Yes

COMPATIBLE WITH EASY-FIX BRACKETS

No

WITH THERMOSTATIC TECHNOLOGY

Yes

**INSTALLATION TOLERANCES** 

min-max wall mount 70-95mm optimum installation depth 82mm

## **CONNECTIONS / FITTINGS**

 $2 \times 3/4$ " female inlets  $2 \times 3/4$ " female outlets

# SPARE PARTS

thermostatic cartridge V-704-34S diverter cartridge C-803-33X/3X.

#### MOUNTING

Wall Mounted

#### PLUMBING SYSTEM SUITABILITY

Gravity System, Pumped System, Combination Boiler, Pressurised System

### **COLLECTION NAME**

DX Elements

# **FINISH**

Chrome







# SPECIFICATION SHEET

COLLECTION: DX ELEMENTS

PRODUCT CODE: ELE-148D/2/SQ-CP

#### MINIMUM OPERATING PRESSURE

0.2 Bar LP (Shower) / 1.0 Bar MP (Bath)

#### MAXIMUM OPERATING PRESSURE

5.0 Bar HP

#### GUARANTEE

15 Year Guarantee

tel: 01934 744466 email: sales@vado.com www.vado.com





# TECHNICAL DRAWING

COLLECTION: DX ELEMENTS

PRODUCT CODE: ELE-148D/2/SQ-CP

