SPECIFICATION SHEET

COLLECTION: CELSIUS
PRODUCT CODE: CEL-128D/2-C/P

Flow Rates
(for "mixed" measurements)

SHOWER TYPE
Shower Valve

WITH ALL-FLOW FUNCTION
No

VALVE TYPE
Concealed

WITH INTEGRATED DIVERTER
No

STYLE
Round, Square

COMPATIBLE WITH STUDFAST
Yes

ORIENTATION
Vertical

WITH BLEED VALVE FOR SYSTEM FLUSH ON INSTALLATION
Yes

HANDLES
3 Handle

SPECIFICATION SHEET

COLLECTION: CELSIUS
PRODUCT CODE: CEL-128D/2-C/P

WITH SHOWER KIT
No

INCLUDES MORTAR / TILE GUARD
Yes

COMPATIBLE WITH EASY-FIX BRACKETS
No

WITH THERMOSTATIC TECHNOLOGY
Yes

INSTALLATION TOLERANCES
min-max wall mount 70-95mm

CONNECTIONS / FITTINGS
2 x 3/4" female inlets 2 x 3/4" female outlets includes 3/4" - 1/2" adaptors

SPARE PARTS
thermostatic cartridge V-001C-PLA 2 x flow cartridge C-301-RTC

MOUNTING
Wall Mounted

PLUMBING SYSTEM SUITABILITY
Gravity System, Pumped System, Combination Boiler, Pressurised System

COLLECTION NAME
Celsius

FINISH
Chrome

MINIMUM OPERATING PRESSURE
0.2 Bar LP (Shower) / 1.0 Bar MP (Bath)

SPECIFICATION SHEET

COLLECTION: CELSIUS
PRODUCT CODE: CEL-128D/2-C/P

FLOW RATE AT 3.0 BAR FLOW PRESSURE

30 l/min

GUARANTEE

15 Year Guarantee

tel: 01934 744466
email: sales@vado.com
www.vado.com

WHERE INSPIRATION FLOWS
TAPS | SHOWERS | ACCESSORIES

VADO

TECHNICAL DRAWING

130

280

70-95

3/4"

3/4"

3/4"

WHERE INSPIRATION FLOWS
TAPS | SHOWERS | ACCESSORIES

VADO